

REPLACEMENT & AFTERMARKET

NEMA 12 E-STOPS



Collaborate / Create / Convey


TABLE OF CONTENTS

Nema 12 E-Stops	02	Product specifications	05
Applications	03	Compliance Standards	06
Key Features	04	The Engineering Advantage	07
		Contact Information	08

© 2026 Fluent Conveyor. All rights reserved.

All content, including text, graphics, and product specifications, is the property of Fluent Conveyor and may not be reproduced, distributed, or transmitted in any form without prior written permission.

NEMA 12 E-STOPS



Nema 12 E-Stops

Indoor industrial environments expose control systems to airborne dust, fiber, and dripping non-corrosive liquids. Uncontrolled machinery movement during an emergency presents immediate personnel risks and regulatory compliance failures across operating zones. Reliable safety circuits must interrupt normal control logic to execute controlled, system-wide shutdowns before material rollback or equipment damage occurs.


NEMA 12 mushroom head E-stops feature a standard 40mm red actuator on a yellow background, utilizing a 1NC contact configuration. Fabricated with IP65 sealing to maintain internal component integrity, these units isolate safety circuits across operator positions, transfer points, and drive units. The architecture integrates directly with safety relays and PLC cabinets to override VFD commands and remove voltage from motor starters.

APPLICATIONS



Recycling Sort Stations

Multi-conveyor sorting systems mandate high-volume manual material handling where multiple feed lines converge. These units wire into safety relay circuits inside the conveyor control panel to execute coordinated, zone-by-zone shutdown sequencing.



Variable Frequency Drive Enclosures

Automated motor control systems dictate belt movement and running speeds. The circuit overrides direct VFD commands to remove voltage from motor starters.



Radial Stacker Conveyors

Pivoting operational profiles demand emergency access at structural articulation points. Units are specified directly at swivel locations and distributed along elevated sections.




Tumble-Back Conveyors

Steep-incline metering establishes risks of uncontrolled material rollback during power removal. Pushbuttons are positioned near the discharge zone to initiate controlled shutdown logic.



Car Shredder Infeed Conveyors:

Extreme heavy-duty applications handling whole vehicles necessitate accessible emergency intervention points. Operators actuate the devices to immediately drop power to motor contactors.



Transfer Stations


Intersecting equipment zones move materials between independent conveyor lines. Enclosures are installed directly at the transfer point to halt overlapping mechanical systems simultaneously.

KEY FEATURES

01

40mm Red Actuator:

Provides high visibility and adequate surface area for palm activation across standard operator stations.



02

Pull-Release Reset Mechanism:

Engineered to require deliberate mechanical action to pull the button head and reset the switch, preventing accidental reactivation of the control logic.

04

IP65 Enclosure Sealing:

Fabricated to block dust, fiber ingress, and dripping non-corrosive liquids in indoor industrial installations.



05

LED Status Indicator:



Integrated into the actuator assembly on illuminated variants to output immediate visual confirmation of the electrical state.

03

1NC Contact Block:

Configured in a normally closed electrical state to integrate directly with safety relay circuits inside the primary control panel.





NEMA 12 E-STOPS SPECIFICATIONS

Parameter	Specification	Notes
Actuator diameter	Standard 40mm	
Reset mechanism	Pull-release pushbutton	
Contact configuration	1NC (normally closed)	Other options available
Illumination	Standard and lamp voltage	
Control circuit voltage	24-240VAC/DC	
Power supply	50/60Hz	
Operating temperature	-25°C to +70°C (-13°F to +158°F)	
Maximum voltage	Up to 600V	Depending on model
Actuation force	4-5 lb	
Mounting height	24-67 inches	Above walking surface
Maximum spacing	100 feet	

COMPLIANCE STANDARDS

Mushroom head E-stops must meet the following regulatory and industry standards for placement, actuation, and electrical configuration.

OSHA 1910.212 and 1910.147

Federal workplace directive mandating integrated emergency stop mechanisms, operational lockout/tagout procedures, and documented maintenance records.

ISO 13850


International function standard requiring Performance Level PLc or SIL 1 ratings, Stop Category 0 or 1 execution, and intentional manual reset actions prior to system restart commands.

ASME B20.1

Primary US conveyor standard establishing 100-foot maximum spacing intervals, 24-67 inch dimensional mounting heights, and 4-5 pound mechanical actuation force requirements.

CEMA Standards

Industry equipment benchmark dictating specific red-on-yellow hardware visibility, physical actuator protrusion, and absolute operational control override priority.



THE ENGINEERING ADVANTAGE


This section outlines the circuit integration methodology behind mushroom head E-stops, covering physical switching characteristics and network architecture to ensure standard-compliant shutdown sequences.

Safety Relay Circuit Integration:

Interrupts the PLC's outputs to drop power to motor contactors when any device in the continuous chain is activated.

VFD Override Logic:

Bypasses primary drive commands to remove voltage directly from motor starters and execute immediate or controlled deceleration.



Tumble-Back Stop Coordination:

Synchronizes the shutdown sequence on steep-incline metering equipment to halt belt movement prior to material rollback.

Tactile Reset Validation:

Requires the operator to manually pull the mushroom head stem to re-establish electrical continuity and clear the fault circuit.

CONTACT INFORMATION

OUR ENGINEERS WILL SPEC THE EXACT PART FOR YOUR SYSTEM

For product specifications, engineering support, or order inquiries, please contact our team using the information provided below. Our specialists are available to ensure accurate recommendations and efficient service for your application requirements.

Reach Us Directly

Email

Send us your questions or requests, and we'll respond promptly.

sales@fluentconveyors.com

Phone

Call us for immediate assistance and technical support.

[+1\(866\) 764-2980](tel:+18667642980)

Business Hours

Monday - Friday

8:00 AM – 5:00 PM MST

Departments

Sales & Quoting

Product pricing, availability, and order placement.

sales@fluentconveyors.com

Customer Service

Product pricing, availability, and order placement.

[+1 \(303\) 390-1228](tel:+13033901228)

Engineering

Technical specs, application review, custom configurations.

engineering@fluentconveyors.com