# REPLACEMENT CONVEYOR MOTORS

/ Collaborate / Create / Convey

Fluent Conveyors uses Nord motors and drives as standard with our equipment. We do supply most manufacturers of drives and motors including Dodge, Sumitomo, Eurodrive and more so we can meet your needs. Our Replacment motors and drives can be had in many different configurations as well as washdown duty and explosion proof. These motor/reducer combos can be ordered as shaft mount or foot mount as well as regular duty, high efficiency, and premium efficiency/inverter duty.

## PARALLEL SHAFT MOTORS/DRIVES



Parallel shaft drives are powerful and efficient drive designs. Fluent provides parallel shaft drives with torque ratings from 970lb-in up to 680,200lb-in. These drives are modular and can be mounted in many different positions so they can conform to fit your needs.

## HELICAL BEVEL MOTORS/DRIVES



The helical bevel gearmotors can be had in single stage or two stage as well as cast steel housing or aluminum housing. These compact and powerful drive systems can come in various stages of carrion resistance and offer torques from 1,593lb-in to 442,500lb-in. The helical bevel gearmotors have many options including foot mounted, torque arm mounted, washdown duty and more.

#### HELICAL INLINE MOTORS/DRIVES



The helical inline motors have a compact design and torsionaly rigid cast iron housing. They are hygienic and have good washdown functionality due to the smooth gear casing. These gearmotors are foot mounted and available in washdown duty as well as explosion proof. The helical gearmotors are available with torque ranging from 88lb-in to 230,000lb-in.

# WORM GEAR MOTORS/DRIVES

#### **MOTOR BRAKES**

#### **REPLACEMENT PARTS**







The worm gearmotors are a versatile and cost effective right angle solution. These drive units can be supplied with corrosion resistant coatings and in wash down duty. Our worm gear motors use a one piece housing wich increases their operational torque and their axial and radial load capacity.

Fluent offers motor brakes to match your drive unit. These can come installed on your drive unit or can be added afterwards. This removes slippage, roll back etc. Fluent conveyors offers replacement parts for gearmotors and drives. We offer everything from housing and seals to gears, roller bearings and shafts. Please contact your original OEM if you are looking for non Nord parts or components.

\*We can use other motors, brands etc if needed. Our standard motors go up to 250 horse power.

FLUENT CONVEYORS, LLC / WWW.FLUENTCONVEYORS.COM / ©COPYRIGHT

(866)764-2980 / SALES@FLUENTCONVEYORS.COM / 1

# Technical Specifications & Motor Modification Options

Please note not all motors/drives can be configured with each option.

79	207 1			_		10 A A							_
T+ + + + + + + + + + +	1 1 A	19 11 11 1 1 1 1		3	6 6 6 6 6 6				8.18		1	+	
· · · · · · · ·		Helical		3	Worm Gear			- 14					
Gearmotor Types				•	Mechanical Var	lable Spee	ed						
		Parallel Shaft											
	× · ·			1	5 5 5 5	10.1			8 - E		1	1	
TOTAL F. C. S. S. A.	9 X 3	all a series	4 4 4 4	- 8		2.1	6	3	1. 19	-			•
	a a 16				(a) (a) (a)				a (a)				
		Asynchronous		•	208/360 Volts								
Gearmotor Types   Motor Types   Power Options   Inverter Speed Range   Mounting Options   Gearmotor Options		Synchronous		•	575 Volts								
											1		
	<ul> <li>Parallel Shaft</li> <li>Types</li> <li>Asynchronous Synchronous</li> <li>Synchronous</li> <li>230/460 Volts 332/575 Volts</li> <li>332/575 Volts</li> <li>5:1 Constant Torce 10:1 Constant Torce 20:1 Constant Torce</li> <li>10:1 Constant Torce</li> <li>20:1 Constant Torce</li> <li>Torque Arm</li> <li>Washdown Duty</li> <li>IP55, IP66</li> <li>Explosion Proof</li> </ul>	8 8 8 8	1		* *		2	· · ·	1				
* 4. 16 16 16 16 16 16	a	(a) a (a) (a) (a)	80 (A) (A) (A)	36	(m) (k) (k) (m)	90 B. (	(a)		к к.			500 - C	* *
	1.1.1						- 26	3	i i	$\mathbf{x}_{i}$	Υ		
Dower Options		230/460 Volts		•	208/360 Volts	8 4 4		4			4		
Fower Options		332/575 Volts		•	575 Volts								
		* * * *						1					_
									4) (4)		1		
1. 1. 1. 1. 1. 1. 1.	1 I F	5:1 Constant Torqu	ue Standard	•	1000:1 Consta	nt Torque	6. 91	3	e (*	8			
Inverter Speed Range	e e po	10:1 Constant Toro	que	• *	Line Powered (	Dnly			e - 141				
	5 R 2			÷		4.4.4			1	3			
		20.1 Constant for	140		an a an an								
				-		1 1 1					1		-
		Shaft Mountad			NEMA Footed								
Mounting Options			(4) (4) (4) (4)			Al Variable Speed //olts //olt							
		lorque Arm	a 2 A A	•	IEC Footed	2 5 3	1	8.1	÷ 3				
		1. 2. 2. 2. 2. 2.		÷		1.1.1	÷	8.0			8		
	× + 765	* * * * *	age of the set					÷ 1					
	•			•	Thermostat								
	•	IP55, IP66		•	Encoder			8 S				-	
	•	Explosion Proof		•	Additional Offe	rings						-	
	•	Sealed Terminal Bo	х		Available Upon			•	e			** **	
			a 31 4 3										
						1.1.1						1. 1	
					er A 14 17					-			
					* * * *		*	÷ 0			1		
	e e e	$X_{i} = X_{i} + X_{i$	$(x_1,\ldots,x_{n-1}) \in \mathbb{R}$		4 4 4 4	1. 1. 1	Ξ.	1	6 8	5			
		×											
					(a) (b) (a) (a)								
* * * * * * * *	n (n n	8 8 8 8 8 <b>8</b>				8 (8 A	÷			÷.,			

			+							2			2	*		185					1			2	2			۰.	1.0						1	1.0	-
*		4		1	1			1		3	÷		5	Ξ	E.		$\hat{\mathcal{H}}$	2	1		2	ŝ		9	$\hat{\mathcal{T}}$			÷	19	+	8	8	*	8	÷		-
-	14	4	4											5		$\mathbb{R}^{n}$		×		1				1										-			-
-					-				( + )			0.0	34			14.1							100.0	$\times$		1.0			1.00	10.1		÷.,	•				
	100				4.				10			-			1.0			×.		: 6.2				3	5												-
				14		3					÷					2		-	÷		a.	÷		×.	8	16	i.					e.					-
						-						1.67					-				-					160				1.0	-					42	
	-																																				
						4				2			4			÷.,	÷	5			2		-	¥.			4				-						
												14					14.1									147											
																																	-				-
																																	1.00		1		
		1																																			
					(4)								1		1.00										÷	140								*		1	
•	FLUENT CONVEYORS, LLC / WWW.FLUENTCONVEYORS.COM / ©COPYRIGHT												2						(866	)764	-298	80 / 8	SALE	S@FL	UEN	тсо	VVEY	ORS	.cov	/ 2	-	-					
				10	31	.9	2			9	*		3	2	1	÷.	3	2			9	÷		9	÷.	14		÷	1	83		5		-	÷		-